



Access 3000 Compact Plus

Access 3000 Compact Plus is a desktop paging system that is simple and easy to use, yet with its powerful expansion options, it can be enhanced to become a fully integrated wireless messaging solution, adding a totally new dimension to the way you communicate.

Technical Specification

System Capacity

- 300 users
- 50 programmable teams with 300 members
- 100 pre-stored messages

Closing Contacts for Automatic Paging

- 5 on-board closing contacts
- Up to 192 closing contacts per system
- All contacts have a programmable message capability

Telephone System Access Connection

- Trunk and Extension Level Access
- Dial pulse signalling and DTMF

RS232 Interface

- TAP, MEP, MSP, AUSTCO and ESPA 4.4.4

Transmitters

Supports a range of transmitters to cater for different frequency and power requirements

Access 3000 System Module Capacity

Up to 27 modules

Access 3000 Compact Plus

Call Formats

- Multitone digital Mk6 and Mk7
- POCSAG (CCIR No.1)

Radio Channels

1 Radio Channel - Up to 4 additional radio channels may be added by the addition of C3EJ slave encoders

Speech

One-way speech available from the paging console and telephone. Access 3000 Compact Plus will also support RPR360 and RPR560 two-way speech systems.

Absence

Self-registered absence by telephone, PC or paging console or automatic rack-registered absence is available on all pager types

Transfer (a paging call to an alternative user)

Each user of their system can have a transfer permanently assigned. The transfer is automatically activated when absence is registered.

Optional Voltage

- 220 - 240V AC 50/60MHz
- 110 - 120V AC 50/60MHz